# Manual guide



# System configuration

### **Power Connection:**

 Connect the power adapter to the setup box and ensure it is securely plugged into a power source.

### **Display Connection:**

 Attach the monitor or screen to the setup box using an appropriate cable (HDMI, VGA, or DisplayPort, as applicable).

### Network Setup:

- For IP Cameras:
  - a. Connect the Power over Ethernet (PoE) switch to the setup box using a LAN cable.
  - b. Ensure the LAN cable is securely connected to both devices.
- For DVR-Based Systems:
  - a. Connect the LAN cable from the DVR to the setup box.

Note: Most of these configurations are typically completed during the setup process with assistance from our representative.

### Camera Installation:

• Connect the cameras to the PoE switch using compatible Ethernet cables. Ensure all connections are firm and the cameras receive power through the PoE switch.

### Power On:

• Turn on the setup box and verify that all connected devices are powered on and functioning.

# Login

### Power On:

• After turning on the ProWatchly setup box, wait for the system to boot up.

## System Login:

• Log in to the system using the default credentials:

Username: Client

Password: helloclient

### **Launch Application:**

• Open the ProWatchly application from the system's desktop or start menu.

## **ProWatchly Login:**

 Log in to the ProWatchly application using the credentials provided by ProWatchly representative.